

## Colocryl Mix

9060

Pigment concentrates for water-based professional and industrial coating systems

### PRODUCT DESCRIPTION

#### Product numbers

89971 ff

#### General

Pigment concentrates for water-based industrial coating systems with very good light fastness, high colour tone and colour strength accuracy as well as high yield.


#### Application area

For tinting water-based industrial coatings by means of automatic dosing units of the ADLERMix system.



### PROCESSING

#### Processing instructions



- Please stir and shake the product well before use (1 minute shaker).
- The temperature of the product and object, and the room temperature must be at least +10 C.
- The product is ready to use.
- Do not use the product as a coating!
- Use only in combination with the base materials recommended by ADLER.
- With ADLER Colocryl Mix mixed varnishes must be processed as specified in the corresponding technical data sheet.
- The product dries quickly in the air. Therefore, empty the containers completely when filling the dosing units.
- Please observe our **ARL 800- Working guideline for working (including care and maintenance) with ADLER Mix, PUR Mix and Color4You dosing machines.**
- Please refer to the corresponding technical data sheets of the products.

#### Cleaning the working equipment

With water immediately after use.



## ORDERING INFORMATION

**Size of trading unit** 1 l container

### Colour shades / Glosslevels



#### Standard colour(s):

Gelb YH (89971)  
 Gelb YN (89982)  
 Oxidgelb OYH (89972)  
 Oxidgelb OYN (89983)  
 Orange OH (89973)  
 Rot RN (89984)  
 Rot RH (89974)  
 Oxidrot ORN (89985)  
 Oxidrot ORH (89975)  
 Rosa MH (89976)  
 Blau G BGH (89977)  
 Violett VN (89988)  
 Blau R BRH (89978)  
 Blau R BRN (89990)  
 Grün GH (89979)  
 Grün GN (89991)  
 Weiß WH (89980)  
 Schwarz SN (89992)  
 Schwarz SH (89981)  
 Oxidrot TOR (89993)  
 Oxidgelb TOY (89994)

## FURTHER DETAILS

### Durability / storage



At least 18 months in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Close opened containers well and use up the content as soon as possible.

### Safety information



The product is only suitable for the industrial and professional use.

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at [www.adler-lacke.com](http://www.adler-lacke.com).